


GATE-TS

Gate-TS is automatic gate with a metal U-shape leaf. It has a fixed passage width. The shape and design of tubular leaf can be customized.



ELEGANT, LIGHT AND MINIMALISTIC PART OF ACCESS CONTROL SYSTEM



Key features:

- Solution for disabled and trolley access;
- Appropriate addition to other TiSO turnstiles (waist-height and full-height);
- Steadfast housing suitable for high traffic areas;
- Can be integrated with any type of access control systems;
- Perfect Fusion of Affordability and High Quality;
- Left hand, right hand and double-sided opening are available;
- Gate housing could be adapted for both indoor and outdoor installations;
- Compatible with Ramped Base Mobile Platform (TiSO Frame-M);
- Extensive Array of Accessories for Customization;
- Wired Remote Control Included in Standard Kit;
- Fail-safe;
- Low Power Consumption.



Technical Specifications:


Model	Gate-TS 650	Gate-TS 900
Width, mm	815	1065
Length, mm	225	
Height, mm	1000	
Passage width, mm	650	900
Mechanism	Servo-driven	
Blocking system	Single electromagnetic brake	
Operation mode	CW (100°) and CCW (100°)	
Emergency mode	Free exit/entry (gate is opening automatically)	
Power fail	Fail safe (gate could be opened manually — standard)	
MCBF, cycles	5 000 000	

Electrical Specifications:

Maximum power consumption, W	55
Voltage	From the AC (100-240)V, 50/60Hz; from a DC source 12 V

Finishing

Standard housing	Brushed SS AISI 304
Available housing	Brushed SS AISI 316; Polished SS AISI 304; Polished SS AISI 316; Powder coated RAL



Specifications are subject to change without prior notice.

