

# FULL-HEIGHT TURNSTILE BICYCLONE W900

Bicyclone turnstile barrier gate designed as a combination extended passage with regular single pedestrian entry point within one full height turnstile. Extended passage ensures smoothless entry of bicycles, wheelchairs, large volume belongs and materials. Can be supplied both in fully welded or assembly (attractive for transportation) design.



## MODEL OF THE FULL-HEIGHT TURNSTILE SERIES GUARANTEES FULL PROTECTION OF THE TERRITORY



20

pers/min

CROSSING CAPACITY  
(through the rotor)



650

mm

PASSAGE WIDTH

900

mm

GATE WIDTH



IP 41/54\*

PROTECTIVE LEVEL



MOTORIZED



BI-DIRECTIONAL

### Advantages

- Bi-directional
- Variety of metal and metal treatment types
- Three arms (angle between bars 120°) and four arms (angle between bars 90°) modifications
- High quality at a cost effective price
- Integration with any type of access control and ID systems
- Low power consumption
- Whisper quiet, low noise operation
- Possibility of customization
- Wide range of accessories
- Complete supply set as a standard
- Fail safe / fail secure

### Standard

- 2 types of LED indication
- Hard Wired remote control
- Fail secure (with manual unlock by key)

### Options

- Any access control systems upon request (e.g. passage counter, RFID/Proximity/BioMetric readers, coin acceptor, push button, barcode and QR-code reader)
- Heating function for external installation (for cold climates)
- Protective canopy or roof
- Fail-safe (automatic opening entrance, exit or both direction when power goes off)

\* first figure is for indoor installation, second figure is for outdoor installation.  
Protection level could be up to IP65 upon request.



www.tiso.global  
+380 (44) 291-21-11  
e-mail: sales@tiso.global



### Technical Specifications:

|   |   |
|---|---|
| Unit width, mm                          | 2515  |
| Unit length, mm                         | 1170  |
| Unit high, mm                           | 2300  |
| Standard mechanism<br>- gate<br>- rotor | Servo-drive (Motorized)<br>Electro-mechanical |
| Available mechanism<br>- rotor          | Servo-drive (Motorized)                       |

#### Controlled by:



access control system;






manual control

#### Electrical Specifications:

- Voltage:
  - from the AC (100-240)V, 50/60Hz;
  - from a DC source 12 V;
- Maximum power consumption 210W per pass

#### Materials

|                   |  |
|-------------------|--|
| Standard housing  | Brushed SS AISI 304  |
| Available housing | Brushed SS AISI 316<br>Polished SS AISI 304<br>Polished SS AISI 316<br>Powder coated RAL |



#### Installation areas:

- Governmental Institutions
- Military Bases
- Nuclear Power Plants
- Production sites (Industrial Plants)
- Commercial areas
- Financial institutions
- Airport Premises
- Business (Office) Centers
- Hotels
- Sport Complexes
- Recreation areas
- Urban areas
- Education Institutions
- others

